



**Specifications**  
Titan Incline Platform Lift

- Model:** IPL500
- Rated Load:** 500 lbs
- Drive:** Rack and Worm Gear / 24 VDC 1/8 HP Motor w/Brake
- Power Supply:** 115VAC, 15Amp Grounded
- Control Circuit:** 24 VDC
- Platform:** 25" X 36"
  - Manual Fold
  - Power Folding Ramps for Entry/Exit
- Travel:** 40' Maximum
- Speed:** 14 FMP
- Controls:** Constant Pressure Rocker Switch on Platform  
Infrared Wireless Call-Send Controls

**Manual Lowering:** Device Provided  
**Safety Design Standards:** Incline Platform Lifts Meets: ASME A18.1-2008, Section 6  
 CAN/CSA B44.1-2011/ASME A17.5-2011  
 Residential Use Only  
 ETL Listed - Control No. 3148125 (Indoor Only)

- Safety Features:**
- Overspeed Governor
  - Upper & Lower Landing Limits
  - Upper & Lower Final Limits
  - Ramp obstruction Sensors
  - Under Platform Safety pan Obstruction Sensors
  - Drive Chassis Obstruction Sensors
  - Non-Skid Platform Surface

LH Shown  
RH Opposite

DRAWN TB	3/3/2012	 3901 Commerce Park Drive Raleigh, NC 27610 (855) 595-0279
CHECKED		
<small>This document is the property of Hammar and is delivered upon the express condition that the contents will not be disclosed or used without the written consent of Hammar.</small>		<b>AmeriGlide Titan Incline Platform Lift</b>
THIRD ANGLE PROJECTION	Tolerance UNO X ±.1 .XX ±.01 .XXX ±.005 Holes ±.005 Ang ±.5°	SIZE FINISH D DWG NO IL500 25x36 TYP
SCALE		REV
SHEET 1 OF 1		